

Understanding: Dual-arm folding of a piece of garment on the CloPeMa testbed

Václav Hlaváč

Czech Technical University, Faculty of Electrical Engineering
Department of Cybernetics, Center for Machine Perception
121 35 Praha 2, Karlovo nám. 13, Czech Republic

hlavac@fel.cvut.cz, <http://cmp.felk.cvut.cz>

CloPeMa team

- ◆ Centre for Research and Technology, Hellas, Thessaloniki (coordinator)
- ◆ University of Glasgow, U.K.
- ◆ Czech Technical University in Prague, Czech Republic
- ◆ University of Genova, Italy
- ◆ Neovision s.r.o., Czech Republic (SME)



Introduction, task formulation

CloPeMa project overview:

CloPeMa (Feb 2012 - Jan 2015) is a STREP which aims at:

- ◆ Advancing the state of the art in the autonomous perception and dual-arm manipulation of all kinds of fabrics, textiles and garments.
- ◆ Novelty of CloPeMa is in its generality – random pile, unfolding, folding sorting.
- ◆ Integration of perception, action, learning, and reasoning.
- ◆ CloPeMa hand.

Our coordinator
Maria Petrou
**1953 - †2012*




This talk:

- ◆ A brief intro to CloPeMa testbed.
- ◆ Demo of the current abilities after Year 2. The much improved polygonal model of the garment.
- ◆ Thoughts about understanding which is needed: scene with garment representation, modeling and reasoning.

CloPeMa Testbed


- ◆ 13 DOF dual-arm robot based on two welding hollow-wrist manipulators Motoman MA 1400.
- ◆ Testbed serves as the experimental platform for soft material manipulation.
- ◆ Openness achieved also through ROS.
- ◆ Sensors: high-resolution optical stereo, 3 Kinects, force/torque sensors between the last manipulator join and the CloPeMa hand.
- ◆ CloPeMa hand: 2 fingers, tactile sensor on one finger, rubbing motion, photometric stereo for detailed analysis of the cloth.



Beating the complexity – divide and conquer

- ◆ Hierarchy of modules of various complexity (top-down).
- ◆ Terminology: (robotic) skill → activity → action → atomic action.
- ◆ Example: T-shirt folding → gravity-folding → lifting the grabbed garment → gripping the garment from the side.
- ◆ The first aim is to compose (plan) a skill automatically from available activities, etc.

- ◆ The second aim is to learn activities, actions empirically with more and more autonomy.



Sutton Dance Writing 1975


Example: Gravity Based Folding

Researcher: Vladimír Petřík, master student, Libor Wagner (project engineer).

Inspired by: J. van den Berg, S. Miller, K. Goldberg, P. Abbeel *Gravity-Based Robotic Cloth Folding*. Proceedings of WAFR 2010, U of California, Berkeley.

Algorithm outline

- ◆ Original g-fold is defined by the folding line and the grasping points.
- ◆ Extended by the orientation of the gripper (input parameter).
- ◆ Improved by the gripper rotation around the folding line (input parameter).
- ◆ It is difficult to find a possible g-fold within the working space when folding the whole garment. (the orientation of the gripper limits the working space).



Gravity Based Folding, manipulation example



Polygonal Model of Clothing (1)

Researcher: Jan Stria (Ph.D. student), V. Hlavac, connection to CloPeMa testbed Libor Wagner (project engineer).

Inspired by: S. Miller, M. Fritz, T. Darrell, and P. Abbeel. *Parametrized shape models for clothing. In Proceeding of the International Conference on Robotics and Automation (ICRA 2011), Shanghai, China, May 2011.*

Overview:

- ◆ **Input:** *a single image of a piece of garment spread on the table.*
- ◆ **Segmentation:** *Gaussian mixture model and GRAB CUT algorithm.*
- ◆ **Contour simplification** *by a polygonal curve approximation, Perez, Vidal, 1994. Suboptimal dynamic programming approach.*
- ◆ **Model mapping:** *locally optimal dynamic programming approach.*
- ◆ **Output:** *Positions of landmark points on the garment contour (e.g. armpit, crotch, endpoints of a trouser leg).*

Polygonal Model of Clothing (2)

◆ Novelty:

- GRAB CUT segmentation parameters learned empirically. No need for the user input in the exploitation phase.
- A different polygonal model of the garment than the state-of-the-art.
- Two orders of magnitude faster performance. Our time = 4 seconds.


◆ Dissemination:

- The initial version of the vision pipeline submitted to ICPR 2014.
- The enhanced version (a more robust model fitting, folded models of garments) submitted to IROS 2014.


Segmentation, contour approximation



original




segmented




polygon

Polygonal models (1)


- ◆ Various categories of clothing can be described by polygonal models.




towel



pants



T-shirt (short s.)



Shirt (long s.)


- ◆ Q: Flexibility?

A: Each garment model is enriched by a probability distribution of inner angles adjacent polygon vertices and relative lengths of polygon edges.


- Modeled by independent normal distributions.
- Learned using the maximum likelihood principle from training data.

Polygonal model (2)


Example: T-shirt, short sleeves.



Polygonal model.




Distribution of inner angles.



Distribution of relative lengths.

Mapping contours to models (1)


- ◆ The observed simplified contour is mapped to the learned polygonal model.



- ◆ Conditions:
 - The mapping preserves ordering of contour points and model vertices in a clockwise direction.
 - Some contour points are mapped to a segment instead of vertex because the simplified contour has less points than is the number of model vertices.


Mapping contours to models (2)

- ◆ The goal is to find the optimal mapping with respect to a cost function.
 - The cost is based on proposed angles and lengths distributions.
 - It would be inefficient to evaluate all possible mappings.
- ◆ Efficient incremental construction of the optimal mapping utilizing dynamic programming.
- ◆ Total matching cost $T_{j,k}^m$ is given by summing previous total cost $T_{i,j}^{m-1}$, vertex cost $V_{i,j,k}^m$, edge cost $E_{j,k}^m$ and segment cost $S_{j,k}$.




Polygonal models of folded garments

- ◆ The model of a particular piece of garment contains possible folds.
- ◆ Polygonal models of a folded garment follow automatically from the initial model and knowledge about performed folds.
- ◆ The vision-based sensing is repeated after each fold performed by a robot to cope with random disturbances.



T-shirt case



towel case

Polygonal model-based folding, video, 2014-02



CloPeMa needs more intelligence

CloPeMa needs ability to:

- ◆ Represent knowledge, including commonsense knowledge.
- ◆ Learn.
- ◆ Plan using a reasoning engine (e.g. a probabilistic Prolog).
- ◆ Divide and conquer strategy: a collection of basic manipulation / perception skills to compose a more complex behaviour autonomously.
- ◆ Sense / act.
- ◆ Dynamics (not treated yet).


Representation:

- ◆ CloPeMa world model: Robot world, scene, a piece of garment.
- ◆ We sense a metric model (depth map, intensity images, tactile, force/torque).
- ◆ Functional garment model, e.g. the presented polygonal one.
- ◆ Physics-based model, pragmatic, task-oriented.
- ◆ Topological model of the garment. 2D manifold embedded in 3D space.

Mechanical model of a piece of fabric, ongoing

Researchers: Vladimír Smutný, Michal Neoral, Zbyněk Šika (Faculty of Mechanical Engineering), Pavel Krsek

- ◆ A piece of a garment is described as a dynamic system.
- ◆ It is similar to the finite element representation.
- ◆ We would like to estimate the model parameters from measurements.
- ◆ Ongoing work. Capturing process is prepared and the preliminary data measured.



Topological model of the garment, ongoing

2D manifold embedded in 3D
Euclidean space.

- ◆ Motivated by Helmut Pottmann's research in computer graphics.
- ◆ Planar Quadrilateral Mesh.
- ◆ Mesh to be learned / re-learned from point clouds sensed by the CloPeMa testbed.
- ◆ The aim is to represent free-folded piece of cloth, e.g. a towel, including a rough representation of the 'invisible'.

